
PERFORMANCE	
FREQUENCY RANGE	DC - 20 GHz
NOMINAL IMPEDANCE	50 Ω
DWV @60Hz [SEA LEVEL]	500 Vrms
VSWR	< 1.22 (DC - 20 GHz)
TEMPERATURE RANGE	-65 / +165 °C
MECHANICAL	
INTERFACES PER	MIL-STD-348
CONTACT RETENTION	6 LBs AXIAL
DURABILITY	500 CYCLES

MATERIALS & FINISHES PER STI SPEC 7.3.1-8


COMPONENT	BASE MATERIAL	FINISH (CODE)
BODY	Ph BRONZE	Au/Cu (G)
CONTACT	BeCu	Au/Cu (G)
DIELECTRIC	PTFE	N/A
COUPLING NUT	Ph BRONZE	Au/Cu (G)
LOCK RING	BeCu	UNPLATED (X)
GASKET	Si RUBBER	N/A

PART NUMBER

1201-27-M5-GG



CABLE PREP



Description:
SMA(M) PLUG, SOLDER/NON-SOLDER CONTACT, NON-MAGNETIC, FOR .086 SEMIRIGID CABLE

DWG NO. OL-1201-27-M5-GG

UNLESS OTHERWISE SPECIFIED:
ALL DIMENSIONS ARE IN INCHES.
ALL DIMESNSIONS ARE AFTER PLATING.
.XXX = ±.005 ALL MACHINED SURFACES MAX.
.XX= ±.01 ANG. ±1/2° FRACTIONAL = ± 1/64
.004 MAX TIR. | AXIS .001

Projection: THIRD ANGLE

SCALE 7:1

4 TURNPIKE ROAD
IPSWICH MA 01938
USA

San-tron

WWW.SANTRON.COM
SANTRON@SANTRON.COM
(978) 356-1585

This drawing and any information or descriptive material set out on it are the confidential and copyright property of SAN-TRON, INC. © and MUST NOT BE DISCLOSED, COPIED, LOANED in whole or part or used for any purpose without the written permission of SAN-TRON, INC.

CAGE: **50896**

REVISIONS

REV.	DESCRIPTION	DISP	DATE	DRAWN	APPROVED
L	REDRAW TO NEW FORMAT	FIFO	9/16/25	NBS	NBS