QUANTUM MICROWAVE

www.QuantumMicrowave.com



Cryogenic Bias Tee


P/N: QMC-CRYOTEE-S0.218SMA-FMF

This Bias Tee design is for cryogenic and room temperature operation is ultra compact. Constructed out of high quality gold plated OFHC Copper for cryogenic use down to 4K.


- Broadband design
- Stackable
- Low Insertion Loss
- Cryogenic functionality

Parameter	Specification	Notes
Frequency	0.2 to 18 GHz	
Insertion Loss	0.25 dB	0.2 to 12 GHz (Cold)
	1 dB	0.2 to 18 GHz
Return loss	-20 dB	0.2 to 12 GHz
	-15 dB	12 to 18 GHz
Connectors In/Out	SMA	DC (F) RF (M) and RF+DC (F)
Housing Material	OFHC / Gold Plated	
Max Voltage	35 V	
Max Current	225 mA	

Measured Data (Typical)




Circuit Schematic



Outline Drawing

P/N: QMC-CRYOTEE-0.218SMA Rev C




QUANTUM MICROWAVE

www.QuantumMicrowave.com



P/N: QMC-CRYOTEE-0.218SMA-FMF Rev C



P/N: QMC-CRYOTEE-0.218SMA-FFF Rev C

